

Model IQ50N (Dialless)

Slimline Telephone



Feature List

- Ringer volume control and ringer light
- Wall mount plate included
- Ten (10) year parts and labour warranty
- Rugged durable construction
- Noise canceling handset microphone
- Hearing aid compatible
- Individual serial number on each unit
- Built-in message waiting and ringer indicator lamp
- Message waiting light built-in to suit many popular PABXs and optional add-ons to suit many other systems (see below table)
- "Tropicguard" protection for humid conditions such as hotel bathrooms



COLOUR SKUS: Top: Red colour (IQ50RN). Left: Cream (IQ50CN). Centre: Light Grey (IQ50GN). Right: Black (IQ50BN).



Brief Specifications of Interquartz IQ50N	
Message Waiting light	Suits: 80 VDC
Ringer Lamp	Neon tube
Dimensions	Width: 68mm; Length: 222mm; Height: 73mm
Ringer	Electronic with Hi/Lo/Off settings; 80 dBA minimum at a distance of 30cm
Weight	The weight of the unit is 0.6kg approximately
Line Cord and Plug	3m line cord & plug (suits RJ11/12/14/45)
Wall Mount Kit	Included
Operating Temp and Humidity	Temperature: 0-40° C; Humidity: 95% RH max, No dew forming
Regulatory Compliance	Complies with current ACA/Austel standards
Acoustic Shock Protection	Instantaneous – 76 dBA (ACA standard 123 dB SPL), Continuous – 103 dBA (ACA standard 120 dBA)
Colour and Material	Red, Black, Grey & Cream ABS plastic