

Model IQ750

Caller ID Handsfree Headset Business Telephone

Feature List

- Headset support suits many headset models from many different vendors
- Caller ID display with on-screen message waiting (suits some systems)
- 120 name and number memories, 20 of which appear on shortcut keys
- Ten (10) year parts and labour warranty
- Supports caller ID call waiting (CIDCW)
- 80 name and number incoming caller list
- Hearing aid compatible
- Data port
- Headset stand and riser (optional)
- Pre-programmable memories to store network feature codes
- Acoustic shock protection for headset and handset
- Volume control for headset and handset earpiece



“Headset Savvy” Features

- Mute key for headset microphone
- Trainer/supervisor “double jacking” mode
- Headset cable polarity switch suits any headset cord
- Headset mic adjustment allows any headset mic type
- Built-in headset amplifier suits a wide range of headset types
- Auto detect circuitry disables handsfree when headset in use
- “Silent ringing” mode selectable so that incoming calls ring only in the headset to reduce office noise
- Mid-call support (change between headset, handsfree and handset during a call)



Brief Specifications of Interquartz IQ750	
Dial Mode	Tone (DTMF)
10 Memory Buttons	32 digits and 16 characters
Pause	User selectable between 1 second and 100 milliseconds
PBX Recall	User selectable Timed Break Recall: 100mS, 200mS, 300ms and 600mS. Factory set to 100mS
Power Source	Line power supports basic functionality, 12VDC power for all features
Redial Function	32 digits
Ringer Lamp	Super-bright LED and Neon tube
Message Waiting light	Suits: Ericsson BP250, Alcatel, Exicom, Fujitsu, NEC, Nortel, Samsung, Lucent Index, Hybrex, LG Aria Panasonic TD500 & TDA Series, Avaya 8700 & IP Office and Aristel 265 System with A4SLU card only Optional: AT&T, Siemens ISDX, Siemens Hicom, Ericsson MD110 and some Hybrex
Dimensions	Width: 160mm; Length: 231mm; Height: 83.5mm
Ringer	Electronic with Hi/Lo/Off settings; 75 dBA at 30cm
Line Cord and Plug	3m line cord & plug (suits RJ11/12/14/45)
Wall Mount Kit	Wall Mount Kit No. 3 (order separately)
Operating Temp and Humidity	Temperature: 0-40° C; Humidity: 95% RH max, No dew forming
Regulatory Compliance	Complies with current ACA/Austel standards
Acoustic Shock Protection	Instantaneous – 110 dB SPL, (ACA standard 123 dB), Continuous – 115 dBA @ 1210 Hz (ACA standard 120 dBA)